



Technological, Ecological, Economical Differences









Company Profile	4-5
High Speed & Low Speed Garment Dyeing Machines	6-11
High Speed & Low Speed Washer Extractors	12-17
Sample Garment Dyeing Machines & Sample Washer Extractors	18-27
Tumble Dryers	28-33
Hydro Extractors	34-35



COMPANY PROFILE

TOLKAR has established in 1969 as a family business regarding to produce textile processing and commercial laundry machines at IZMIR, Camdibi. From the very first date, continuous development, better quality and customer satisfaction have made up a principle by TOLKAR where at the present day constitute from 2 splendid innovative production factories in İZMİR Ataturk Industrial Zone along with distributorship of the leader manufacturers of their sectors for supplementary products and more than 300 employees of its Group Companies. TOLKAR has its own reputation in the world by reaching the production capacity of 3500 machines per year of various models and exports more than 70 countries abroad. Besides, 16 Regional Branches with their Service Managements in Turkey and more than 25 distributors with their Service Managements in abroad ensure the fastest sales and after sales servicing facilities to their customers.

Along the stage of development, TOLKAR is devoted itself to differ as technological, ecological and economical supremacies. Utilization of latest technologies and techniques in production, TOLKAR performs from starting up the design phase, consequent research & development, prototype production, factory tests, field tests and mass production by accomplishing the mentioned triple mission. All revolutionary inventions those differs as technological, ecological and economical supremacies;

have been protected with their Patents in all over the world. All our innovations offer to our customers uncompromised and inapproachable savings where at the same time minimize the effluent in order to protect the environment for a clean world to the next generations.

TOLKAR provides all capacities of commercial laundry & textile processing machines and equipments right along side the distributorship of the leader brands in their sector such as TRANSFERON, BIKO, COLMAC, SPEEDQUEEN, CHICAGO and RENZACCI. In 2008, after acquisition of SMARTEX and its "Smart Balancing System", TOLKAR becomes the unique company who has the capability of manufacturing very high speed washer extractors by exerting 400 G force while spinning. Yet as the first and only producer of the new innovation introduced PolyRib ECO Drum, TOLKAR is proud to offer SMARTEX MIRACLE series which saves dramatically 50 % from the water, chemicals and heating energy. In 2013, TOLKAR is proud to announce SMARTEX Miracle + TS which has in built water recovery tank system that saves additional 25 % water saving additional to SMARTEX Miracle series.

With the consciousness of change alone is unchanging, TOLKAR will perpetuate the leadership in accordance with its mission to next generations. Feel like a star with TOLKAR.




SMABTEXY®













SMARTEX MIRACLE High Speed Garment Dyeing Machines

120 - 135 - 150 - 225 - 340 - 500 kg

	Miracle GD 120	Miracle GD 135	Miracle GD 150	Miracle GD 225	Miracle GD 340	Miracle GD 500		
(kg)	120	135	150	225	340	500		
(lt)	1.125	1.320	1480	2.280	3.398	4.800		
(mm)	1.070	1.140	1240	1.480	1.720	1.720		
(mm)	1.294	1.290	1.255	1.420	1.530	2.120		
	Adjustable-Variable							
(rpm)	820	790	760	700	645	645		
(G)	400	400	400	400	400	400		
(Kw)	18,5	18,5	22	30	18,5	22		
(mm)	1.530	1.585	1.750	1.915	2.175	2.200		
(mm)	2.415	2.448	2.480	2.275	2.550	3.650		
(mm)	2.030	2.056	2.120	2.530	2.730	2.550		
(mm)	2.370	2.456	2.461	2.845	3.110	3.650		
(kg)	2.230	2.700	2.980	4.530	6.300	7.360		
	(lt) (mm) (mm) (rpm) (G) (Kw) (mm) (mm) (mm)	(kg) 120 (kg) 120 (lt) 1.125 (mm) 1.070 (mm) 1.294 (rpm) 820 (G) 400 (Kw) 18,5 (mm) 1.530 (mm) 2.415 (mm) 2.030 (mm) 2.370	(kg) 120 ED 135 (lt) 1.125 1.320 (mm) 1.070 1.140 (mm) 1.294 1.290 (rpm) 820 790 (G) 400 400 (Kw) 18,5 18,5 (mm) 1.530 1.585 (mm) 2.415 2.448 (mm) 2.030 2.056 (mm) 2.370 2.456	Kg) 120 GD 135 GD 150 (kg) 120 135 150 (lt) 1.125 1.320 1480 (mm) 1.070 1.140 1240 (mm) 1.294 1.290 1.255 Adjustable-Varia (rpm) 820 790 760 (G) 400 400 400 (Kw) 18,5 18,5 22 (mm) 1.530 1.585 1.750 (mm) 2.415 2.448 2.480 (mm) 2.030 2.056 2.120 (mm) 2.370 2.456 2.461	Kg) 120 GD 135 GD 150 GD 225 (kg) 120 135 150 225 (lt) 1.125 1.320 1480 2.280 (mm) 1.070 1.140 1240 1.480 (mm) 1.294 1.290 1.255 1.420 Adjustable-Variable (rpm) 820 790 760 700 (G) 400 400 400 400 (Kw) 18,5 18,5 22 30 (mm) 1.530 1.585 1.750 1.915 (mm) 2.415 2.448 2.480 2.275 (mm) 2.030 2.056 2.120 2.530 (mm) 2.370 2.456 2.461 2.845	Kg LO CD LO LO<		



1:2-1:2,5 LIQUOR RATIO dry garments




POLYRIB ECO DRUM SYSTEM

less water, chemicals, steam and waste water

%40 less less dyes | electric energy

















SPIN DYE SYSTEM

High speed dyeing with Spin Dye Jet Spraying Technology Prevents all crease marks, abrassion and undesired mechanical effects.

Sustainable dyeing technol-

400 G **EXTRACTION FORCE**

%20 less drying energy and time

SMART BALANCING

totally vibration free extraction eliminates the risk of damages

TOLKAR ULTIMATE CONTROL SYSTEM


remote access enables updates of parameters or versions, recipe preparation, upload/download, recipe transfer to desired machines

USB programme and parameter transfer between machines 100 recipes, 100 steps

reporting amount of dyed garments, consumption of water, electric, steam, loading and operating times **(Optional)**

PLC Controlled Touchscreen panel





DRUM

Continous level measurement Progressive dosing Main tank with indirect steam heating Easy tank cleaning with filtering system Manual interference

Indirect Steam Heating

Automatic precision of water, chemical and steam intake in accordance with Automatic Weighing System (Optional)

DOOR

(Optional)

Easy and automatic loading

(Optional)

Acquisition System



TOLKAR MENSA Low Speed Garment Dyeing Machines

160 - 300 - 400 - 500 kg

		MENSA 1658	MENSA 3179	MENSA 3815	MENSA 4948
Nominal Capacity	(kg)	160	300	400	500
Drum Volume	(lt)	1.658	3.179	3.818	4.948
Drum Diameter	(mm)	1.300	1.800	1.800	1.880
Drum Depth	(mm)	1.250	1.250	1.500	1.790
Motor Power	(Kw)	7,5	15	15	22
Gear Box Direct Drive (Optional)	(Kw)	15	18,5	18,5	22
Width	(mm)	2.035	2.990	2.425	2.650
Depth	(mm)	2.845	2.830	3.285	3.805
Height	(mm)	2.365	2.600	2.990	2.660
Weight	(kg)	2.900	6.000	6.350	8.400

















Belt-**Pulley Drive System**

DIRECT DRIVE SYSTEM

Eliminates the needs of belt-pulley systems No V-belt adjustments needed

(Optional)

150 RPM

PRE-**EXTRACTION**

(Optional)

TOLKAR ULTIMATE **CONTROL SYSTEM**

remote access enables updates of parameters or versions, recipe preparation, upload/download, recipe transfer to desired machines

USB programme and parameter transfer between machines 100 recipes, 100 steps

reporting amount of dyed garments, consumption of water, electric, steam, loading and operating times (Optional)

316 L **INNER DRUM**

PLC Controlled Touchscreen panel

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice





(Optional)

(3rd tank optional)

Automatic Weighing

(Optional)

(Optional)











SMARTEX MIRACLE High Speed Washer Extractors

		Miracle 120	Miracle 135	Miracle 150	Miracle 225	Miracle 340	Miracle 500		
Nominal Capacity	(kg)	120	135	150	225	340	500		
Drum Volume	(It)	1.125	1.320	1.480	2.280	3.398	4.800		
Drum Diameter	(mm)	1.070	1.140	1.240	1.480	1.720	1.720		
Drum Depth	(mm)	1.294	1.290	1.255	1.420	1.530	2.120		
Washing Speed		Adjustable-Variable							
Max. Extraction	(rpm)	820	790	760	700	645	645		
Max. G Force	(G)	400	400	400	400	400	400		
Motor Power	(Kw)	18,5	18,5	22	30	18,5	22		
Width	(mm)	1.530	1.585	1.750	1.915	2.175	2.200		
Depth	(mm)	2.415	2.448	2.480	2.275	2.550	3.650		
Height	(mm)	2.030	2.056	2.120	2.530	2.730	2.550		
Height in Tilted Position	(mm)	2.370	2.456	2.461	2.845	3.110	3.650		
Weight	(kg)	2.230	2.700	2.980	4.530	6.300	7.360		
Weight	(kg)	2.230	2.700	2.900	4.550	0.300	7.300		



1:2,5-1:3 LIQUOR RATIO dry garments



POLYRIB ECO DRUM SYSTEM

0/050 less water, chemicals, steam and waste water

0/40 less electric energy



SPIN WASH SYSTEM

Washing with Spin wash Jet Spraying Technology

Prevents all crease marks, abrassion and undesired mechanical effects.

Sustainable washing technology.



400 G **EXTRACTION FORCE**

%20 less drying energy and time

SMART BALANCING

totally vibration free extraction eliminates the risk of damages









TOLKAR ULTIMATE CONTROL SYSTEM

remote access enables updates of parameters or versions, recipe preparation, upload/download, recipe transfer to desired machines

USB programme and parameter transfer between machines

100 recipes, 100 steps

reporting amount of dyed garments, consumption of water, electric, steam, loading and operating times **(Optional)**

PLC Controlled

Touchscreen panel





INNER DRUM

WEIGHING **SYSTEM**

Automatic precision water, chemical and steam intake in accordance with Automatic Weighing
System
(Optional) LOADING **DOOR**

(Optional)

TILTING

Easy and automatic loading

(Optional)

System Controls And Data Acquisition System



TOLKAR HYDRA Low Speed Washer Extractors

160 - 300 - 400 - 500 kg

		HYDRA 1658	HYDRA 3179	HYDRA 3815	HYDRA 4948
Nominal Capacity	(kg)	160	300	400	500
Drum Volume	(lt)	1.658	3.179	3.818	4.948
Drum Diameter	(mm)	1.300	1.800	1.800	2.050
Drum Depth	(mm)	1.250	1.250	1.500	1.500
Motor Power	(Kw)	7,5	15	15	22
Gear Box direct drive (Optional)	(Kw)	15	18,5	18,5	22
Width	(mm)	2.035	2.990	2.425	2.650
Depth	(mm)	2.365	2.600	2.990	3.805
Height	(mm)	2.845	2.830	3.285	2.660
Weight	(kg)	2.900	6.000	6.750	8.400

















Belt-**Pulley Drive System**

DIRECT DRIVE SYSTEM

Eliminates the needs of belt-pulley systems. No V-belt adjustments needed. (Optional)

150 RPM

PRE-**EXTRACTION**

(Optional)

TOLKAR ULTIMATE

remote access enables updates of parameters or versions, recipe preparation, upload/download, recipe transfer to desired machines

USB programme and parameter transfer between machines

100 recipes, 250 steps

reporting amount of dyed garments, consumption of water, electric, steam, loading and operating times (Optional)

5 mm 304 L **INNER DRUM**

5 mm 316 T Titanium (optional)

PLC Controlled Touchscreen panel

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice

Hydra



INNER DRUM

Easy replacement of the protection sheet (Optional)

KITCHEN WITH SINGLE **TANK**

(1st 2nd and 3rd tank optional)

Covering for all **Columns** and Front

Plate (Optional)

SYSTEM

Automatic precision water, chemical and steam intake in accordance with Automatic Weighing System

(Optional)

LOADING **DOOR**

(Optional)

System Controls And Data Acquisition System





SMARTEX®





TOLKAR MIRACLE Sample Dyeing Machines

4-10-12-20-25-30-40-50-60 kg

		Miracle GD 4	Miracle GD 10	Miracle GD 12	Miracle GD 20	Miracle GD 25	Miracle GD 30	Miracle GD 40	Miracle GD 50	Miracle GD 60
Nominal Capacity	(kg)	4	10	12	20	25	30	40	50	60
Drum Volume	(It)	40	100	120	208	254	300	400	500	600
Drum Diameter	(mm)	420	610	610	762	762	762	915	915	1.092
Drum Depth	(mm)	300	345	410	460	550	662	610	760	642
Motor Power	(kw)	1,5	1,5	2,2	3	4	4	5,5	7,5	11
Width	(mm)	715	825	825	990	990	990	1.180	1.180	1.460
Depth	(mm)	980	860	970	1.030	1.155	1.300	1.345	1.525	1.590
Height	(mm)	1.060	1.190	1.190	1.450	1.450	1.450	1.780	1.780	2.000
Weight	(kg)	280	350	390	595	700	770	1.125	1.230	2.250



1:2-1:3 LIQUOR RATIO dry garments



POLYRIB ECO DRUM SYSTEM

% less water, chemicals, steam and waste water

%20 %40 less electric energy











PLC



SPIN DYE SYSTEM

High speed dyeing with Spin Dye Jet Spraying Technology

Prevents all crease marks, abrassion and undesired mechanical effects.

Sustainable dyeing technology.

300 G EXTRACTION FORCE

TOLKAR ULTIMATE CONTROL SYSTEM

remote access enables updates of parameters or versions, recipe preparation, upload/download, recipe transfer to desired machines

USB programme and parameter transfer between machines 100 recipes, 100 steps

reporting amount of dyed garments, consumption of water, electric, steam, loading and operating times (Optional)


Controlled Touchscreen Control

Panel

316 L INNER DRUM

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice





Indirect Steam Heating Sample recipe ---> Bulk Recipe

Direct recipe transfer from sample to bulk machines without any correction.

CHEMICAL/DYE **INLET**

(1st 2nd and 3rd tank optional)

Steel Outer **Structure**

SYSTEM

Automatic precision of water, chemical of water, chemical and steam intake in accordance with Automatic Weighing System (Optional)

System Controls And Data Acquisition System



TOLKAR MENSA Sample Dyeing Machines

10 - 12 - 20 - 25 - 30 - 40 - 50 - 60k - 110 kg

		Mensa 10	Mensa 12	Mensa 20	Mensa 25	Mensa 30	Mensa 40	Mensa 50	Mensa 60	Mensa 110
Nominal Capacity	(kg)	10	12	20	25	30	40	50	60	110
Drum Volume	(lt)	100	120	208	254	300	400	500	600	1.100
Drum Diameter	(mm)	610	610	762	762	762	915	915	1.092	1.320
Drum Depth	(mm)	345	410	460	550	662	610	760	642	805
Motor Power	(kw)	1,5	2,2	3	4	4	5,5	7,5	11	22
Width	(mm)	825	825	990	990	990	1.180	1.180	1.460	1.720
Depth	(mm)	860	970	1.030	1.155	1.300	1.345	1.525	1.590	2.092
Height	(mm)	1.190	1.190	1.450	1.450	1.450	1.780	1.780	2.000	2.470
Weight	(kg)	350	390	595	700	770	1.125	1.230	2.250	4.600









300 G

EXTRACTION FORCE









TOLKAR ULTIMATE CONTROL SYSTEM
remote access enables updates of parameters or versions, recipe preparation, upload/download, recipe transfer to desired machines

USB programme and parameter transfer between machines 100 recipes

reporting amount of dyed garments, consumption of water, electric, steam, loading and operating times (Optional)

316 L **INNER DRUM**

HEAT **EXCHANGER**

> Indirect Steam Heating

Fully Stainless Steel Outer **Structure**

PLC Controlled Touchscreen panel

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice





SOVEREIGN RECIPE ACCORDANCE

Sample recipe ---> Bulk Recipe

Direct recipe transfer from sample to bulk machines without any correction.

SINGLE CHEMICAL/DYE **INLET**

(1st 2nd and 3rd tank optional)

AUTOMATIC WEIGHING **SYSTEM**

Automatic precision of water, chemical of water, chemical and steam intake in accordance with Automatic Weighing System (Optional)

SCADA

System Controls And Data Acquisition System



TOLKAR MIRACLE Sample Washer Extractors

4 - 10 - 12 - 20 - 25 - 30 - 40 - 50 - 60 kg

		Miracle 4	Miracle 10	Miracle 12	Miracle 20	Miracle 25	Miracle 30	Miracle 40	Miracle 50	Miracle 60
Nominal Capacity	(kg)	4	10	12	20	25	30	40	50	60
Drum Volume	(lt)	40	100	120	208	254	300	400	500	600
Drum Diameter	(mm)	420	610	610	762	762	762	915	915	1.092
Drum Depth	(mm)	300	345	410	460	550	662	610	760	642
Motor Power	(kw)	1,5	1,5	2,2	3	4	4	5,5	7,5	11
Width	(mm)	715	825	825	990	990	990	1.180	1.180	1.460
Depth	(mm)	980	860	970	1.030	1.155	1.300	1.345	1.525	1.590
Height	(mm)	1.060	1.190	1.190	1.450	1.450	1.450	1.780	1.780	2.000
Weight	(kg)	280	350	390	595	700	770	1.125	1.230	2.250



1:2,5-1:3 LIQUOR RATIO dry garments



POLYRIB ECO DRUM SYSTEM

0%50 less water, chemicals, 0%40 less steam and waste water

electric energy













SPIN WASH SYSTEM

Washing with Spin wash Jet Spraying Technology

Prevents all crease marks, abrassion and undesired mechanical effects.

Sustainable washing technology.

300 G **EXTRACTION FORCE**

TOLKAR ULTIMATE **CONTROL SYSTEM**


remote access enables updates of parameters or versions, recipe preparation, upload/download, recipe transfer to desired machines

USB programme and parameter transfer between machines 100 recipes, 100 steps

reporting amount of dyed garments, consumption of water, electric, steam, loading and operating times **(Optional)**

PLC Controlled Touchscreen panel







TOLKAR HYDRA Sample Washer Extractors

10 - 12 - 20 - 25 - 30 - 40 - 50 - 60 - 110 kg

		Hydra 10	Hydra 12	Hydra 20	Hydra 25	Hydra 30	Hydra 40	Hydra 50	Hydra 60	Hydra 110
Nominal Capacity	(kg)	10	12	20	25	30	40	50	60	110
Drum Volume	(It)	100	120	208	254	300	400	500	600	1.100
Drum Diameter	(mm)	610	610	762	762	762	915	915	1.092	1.320
Drum Depth	(mm)	345	410	460	550	662	610	760	642	805
Motor Power	(kw)	1,5	2,2	3	4	4	5,5	7,5	11	22
Width	(mm)	825	825	990	990	990	1.180	1.180	1.460	1.720
Depth	(mm)	860	970	1.030	1.155	1.300	1.345	1.525	1.590	2.092
Height	(mm)	1.190	1.190	1.450	1.450	1.450	1.780	1.780	2.000	2.470
Weight	(kg)	350	390	595	700	770	1.125	1.230	2.250	4.600











5 mm 304 INNER **DRUM**





TOLKAR ULTIMATE CONTROL SYSTEM

remote access enables updates of parameters or versions, recipe preparation, upload/download, recipe transfer to desired machines

USB programme and parameter transfer between machines 100 recipes

reporting amount of dyed garments, consumption of water, electric, steam, loading and operating times **(Optional)**



316 T Titanium **INNER DRUM** (Optional)

PLC Controlled Touchscreen panel

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice

Hydra



Steel Outer **Structure**

Sample recipe ---> Bulk Recipe

Direct recipe transfer from sample to bulk machines without any correction.

INLET TANK

Automatic precision of water, chemical of water, chemical and steam intake in accordance with Automatic Weighing System (Optional)

Acquisition System





SMARTEX®







remote access enables updates of parameters or versions, recipe preparation, upload/download, recipe transfer to desired machines

USB programme and parameter transfer between machines FULL COLORFULL 4,3" TFT SCREEN MANUAL CONTROL

15 programmable recipes.

reporting amount of dyed garments, consumption of electric, steam, gas, loading and operating times (Optional)

Quick heating & easy maintenance

(available with steam heated machines)

CONTROLLED **DRYING**

Cooling System

Prevents wrinkles and hardening

ROTATION





ALL MODELS WITH GAS HEATING OPTION

FORWARD TILTING FOR EASY UNLOADING

(Standart with models 2700 – 4069 - 5070)

304
INNER DRUM
316 L
INNER DRUM
(Optional)

SYSTEM
Direct steam
praying onto the

spraying onto the (Optional)

CONTROL (Optional)

Easy and automatic loading (For models 2700 – 4069 – 5070) (Optional)




TOLKAR CARINA Tumble Dryers

15 - 22 - 30 - 45 - 60 - 75 - 135 - 200 - 250 kg

T=LKIND





		Carina 305	Carina 450	Carina 605
Heating Type		Elect. / Stm. / Gas	Elect. / Stm. / Gas	Elect. / Stm. / Gas
Capacity 1/20 - 1/15		15/20	22/30	30/40
Drum Volume	(lt)	305	450	605
Drum Motor Power	(Kw)	0,75	0,75	0,75
Fan Motor Power	(Kw)	0,75	0,75	0,75 / 1,5 / 0,75
Electric Thermal Power	(Kw)	14	18	21
Steam Consumption	(kg/h)	38	38	44
Gas Thermal Power	(Kcal/h)	18.000	23.000	25.000
Air Flow	(m^3/h)	1.300	13.00	1.500
Width	(mm)	970	970	1.040
Depth	(mm)	870	1100	1.215
Height	(mm)	1.750 / 1.750 / 1.910	1.750 / 1.750 / 1.910	1.775 / 1.860 /1.910
Height in Tilted Position	(mm)			
Weight	(kg)	280	295	365

Carina 905	Carina 1200	Carina 1500	Carina 1500*
Elect. / Stm. / Gas	Elect. / Stm. / Gas	Elect. / Stm. / Gas	Stm. / Gas
45/60	60/80	75/100	75 / 100
905	1198	1492	1492
1,5	3	3	3
1,5 / 2,2 / 2,2	2,2	2,2/3/3	3/3
42	42	42	
81	95	110	110
33.000	37.125	44.550	44.550
3.900 / 4.500 / 4.500	4.500 / 6.400 / 6.400	4.500 / 6.400 / 6.400	6.400 / 6.400
1.610	1610 / 1.640 / 1.610	1.610 / 1.640 / 1.610	1.640 / 1.610
1.440	1.700	1.960	1.960
2.060 / 2.250 / 2.346	2.060 / 2.250 / 2.346	2.060 / 2.250 / 2.346	2.525 / 2.645
			2.553 / 2.889
650	725	900	1.100

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice * For forward tilting option





Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice

2.850 / 3.100

2.989 / 3.280

2.300

Height in Tilted Position

(kg)

Weight

3.390 / 3.583

3.390 **/** 3.689 3.910



The same of the

TOLKAR LIBRA Hydro Extractors

12 - 100 kg

Sample Hydro E	xtractor	Libra 12
Capacity	(kg)	12
Drum Diameter	(mm)	450
Drum Depth	(mm)	400
Inner & Outer Drum		304 L Stainless Steel
Motor Power	(kw)	2,2
Main Body		Cast Iron
Legs		C 1040 Steel
Door		304 L Stainless Steel with Pneumatic Control
Control Panel		Door Switch Controlled Operation
Brake System		Manual Break Pedal
Extraction Speed	(rpm)	900
Water Drain	(inch)	1
Width	(mm)	1.350
Height	(mm)	825
Depth	(mm)	915
Weight	(mm)	170



C1040 Legs

Manual Break Pedal Door Switch Controlled Operation 304 L Stainless Steel





1.845

1.200

(mm)

(mm)

Depth

Weight

EGE ORMAN VAKFI **TOLKAR Memorial Forest Constituted** with Our Esteemed Customers Some of Our Business Partners Contributed to Our Social Responsibility Project **SKENT** SARAR **Migros** ZAMBAH MARTI Онимель **IMPERIAL SAVOY** Λ C I B Λ D E M *TOFAS* VON PALACE HUTTE K dinament **LUKIL** Lösemili Çocuklar Vakfı Özdilek AMAN "Simsicak bir gelenek **3**bp **⋘Koç** AHCIVAN" AURUM **OZYER** swissôtel **47** GÜRAL OZORLU Turyağ KOZSA LETOONIA **Sheraton VESTEL** $\mathbf{X} \circ \mathbf{S}$ △ CENGÌZ **EROĞLU** و بحدادهی HOTEL GOLD Prestige Japarel MAJESTY SPORTS INTERNATIONAL Arvind TRABZON RAMADA Wash GLŌRIA UCO Raymond winstone



RAMADA HOTELS&





















KICHMOND

Eurest Services

ER-BA TEKSTIL



BERENDSEN





DEDEMAN

Akay



LC Walkiki

AG ADRIANO GOLDSCHMIED

KORUMAR

ROCKS



KATYA HOTEL



AKBULUT











-Beta-

















We sincerely thank you for contributing to Aegen Forest Trust TOLKAR Memorial Forest and to the Nature by choosing our products...







Countries Exporting to

Greenland Poland Afganistan Albania Portugal Hungary Algeria India Qatar Armenia Indonesia Romania Aruba Russia Iran Rwanda Azerbaijan Iraq Bangladesh Ireland Saudi Arabia

Belarus Israel Serbia
Belgium Italy Slovakia
Bosna Herz. Jordan South Africa

Kazakhstan Bulgaria Spain China Kenya Sri Lanka Colombia Korea Sudan Croatia Sweden Kosovo Denmark Kygrzystan Syria Lebanon Tanzania Dominican Rep. Libya Tunisia Egypt

England Mauritius Turkmenistan

Macedonia

Estonia Mexico UAE
Ethiopia Morocco Ukraine
France Netherlands USA

Georgia Norway Uzbekistan Germany Oman Vietnam

Ghana Pakistan
Greece Phillippines

www.tolkar.com.tr

info@tolkar.com.tr



Egypt





Tunisia







A.O.S.B. 10036 Sokak No:6 35620 Çiğli - İzmir Tel: +90 232 376 8500 (pbx) • Fax: +90 232 376 7658 info@tolkar.com.tr

www.tolkar.com.tr











